

### 3. Sales Information

---

#### A.1 Basic Information

**Main Box, Top cover, Rating Label, User's Manual, Quick-Reference Guide, Driver, Driver Label**

**Brand : SAMSUNG**

**Models : ML-84/85/85G, QL-84/85/85G**

**English Language Driver Label, Rating Label**

2-Language Laser Label

5-Language Main Box, LSU Caution

4-Language Hot Fuser

**With or without cable**

#### A.2 SELECTABLE INFORMATION

**Rated Voltages : AC 110V ~ 120V (Engine Board, Fuser)**

AC 220V ~ 240V (Engine Board, Fuser)

**Rating Labels : 110V ~ 120V UL/CSA/FCC/CDRH**

**(English)** 220V ~ 240V TUV/CE/CB/SEMKO/NEMKO/DEMKO/C-Tick

**Power Cords : Australian, European, United Kingdom, American**

**User's Manual, Quick Reference Guide, Driver Language:**

English, French, German, Italian, Spanish

**Cassette setting : A4, Letter**

#### A.3 OPTION INFORMATION

**Memory (RAM) : 0.5MB SIMM 1MB SIMM**

**Serial Interface : Serial Interface Board (except ML-85G)**

**Second Cassette Feeder : 250 sheets (ML-85 only)**

**IEEE 1284 Cable**

### 3. Sales Information

---

#### A.4 FEATURES

- 1). **Non-Magnetic Single-Component System (Developer)**
- 2). **Ozone-Free Roller Charging And Transfer Process**
- 3). **Used Toner Recycling**
- 4). **EPA Standard Power Saving compliant**
- 5). **Cartridge Life: 5,000 sheets @ 5% Coverage**
- 6). **Low Noise (without Fan Motor)**

#### A.5 Weak points:

- a) **At low temperatures, a ghost appears which is the diameter of the OPC Drum.**
  - >Just after installation or after a long period of inactivity.
  - Attach a warning message on the developer unit to avoid out-of-specification environmental conditions.
- c) **During printing, black spots appear with the diameter of the OPC Drum.**
  - > This can be resolved through Message printing